

edge extending laterally, said relatively large lower portion of said blocking member extending downwardly from said upper edge to terminate along a laterally extending bottom edge which is adjacent to and substantially parallel to the ground between said first and second side edges of said relatively large lower portion of said blocking member, said relatively smaller upper portion of said blocking member extending upwardly from said upper edge of said relatively larger lower portion of said extending upwardly from said upper edge of said relatively larger lower portion of said blocking member to terminate at an upper laterally extending edge of said relatively smaller upper portion of said blocking member which extends adjacent to and substantially parallel to said cross-bar of said goal post framework, said relatively smaller upper portion of said blocking member having a first upwardly extending side edge spaced apart inwardly from said first side leg of said goal post framework and located inwardly from said first side edge of said relatively larger lower portion of said blocking member, said relatively smaller upper portion of said blocking member also having a second upwardly extending side edge spaced apart inwardly from said second side leg of said goal post framework and located inwardly from said second side edge of said relatively larger lower portion of said blocking member, wherein said blocking member comprises a net, wherein said side edges of said relatively larger lower portion of said blocking member net are each spaced apart inwardly from their respective first and second side legs of said goal post framework a distance of substantially three feet, including a first doubled-back cord inwardly of and closely adjacent to said first side edge of said relatively larger lower portion of said blocking member net, said first doubled-back cord also extending laterally inwardly of and closely adjacent to a portion of said upper edge of said blocking member